XETAWAVE
CUSTOM RF SOLUTIONS

XETAEDGE24

2.4 GHz Ethernet Radio

Industrial edge computer with SDR · unlicensed 2.4 GHz



5.3Mbps
Max over-the-air rate

1W
RF output (+30 dBm)

24mi
Range

Mesh
Mobile Ad-hoc Networking

The **XetaEdge24** combines the power of the **XetaEdge** platform with the **Xeta24** radio to create a highly capable and flexible industrial Edge Computing solution. Featuring an integrated Software Defined Radio (SDR) operating in the unlicensed 2.4 GHz frequency band and running the Debian operating system, the **XetaEdge24** is part of XetaWave's latest generation of industrial radios.

Built on a 100% open-source architecture, the **XetaEdge24** enables rapid deployment of both existing and custom applications. Supported software includes eACM, Ignition Edge, CODESYS, PLC Shift, Node-RED, and many others, allowing seamless integration with field devices such as **meters**, **ROCs**, and **PLCs**.

All **Xeta24** radios across the uTasker, Linux, Debian, XetaEdge, and XetaCell product families are fully over-the-air compatible. For applications requiring simultaneous transmit and receive capability, the **XetaEdge24x24** model provides full-duplex operation.

KEY FEATURES

High Speed
57 kbps to 5.3 Mbps over the air; higher throughput with payload compression and Enhanced MultiPoint.

Dual Mode
Frequency hopping spread spectrum and single channel operations in unlicensed 2.4 GHz ISM band.

Adjustable RF Output
Transmit output power from 10 mW (+10 dBm) up to 1 W (+30 dBm).

Network Types
Point-to-Point, Point-to-Multipoint, CSMA Peer-to-Peer, Enhanced MultiPoint, and Mesh.

Secure
Over-the-air payload and overhead encryption using 128-bit or 256-bit AES.

Selective Modulation
Multiple MSK, PSK, and QAM modulations.

MultiSpeed
Endpoints communicate at different RF data rates with the Access Point.

Diagnostics
Monitoring TX/RX statistics (noise, RSSI and more), voltage, and temperature over SNMP and Modbus.

Apps
AUTOSOL eACM, Node-RED, Inductive Automation Ignition Edge, PLC Shift, and more apps supported.

Cellular
XetaCell24 models with LTE cellular and 2.4 GHz ISM capability are available.

Dual Channel
Dual channel radios covering the same or different frequency bands are available.

GPS
Models with an integrated GPS are available.

258 South Taylor Avenue | Louisville, CO 80027 | 303-447-2745 | sales@xetawave.com www.xetawave.com

Hardware & Transmitter Specifications

PROCESSING

CPU	ARM Cortex-A8 @ 1 GHz
OS	Debian
RAM / Flash	1 GB / 16 GB

POWER @ +12 VDC

Transmit	235 mA
Receive	190 mA
Idle	176 mA

INTERFACES

Power	2-pin Phoenix · +10 to +32 Vdc
Ethernet	2× RJ45 · 10/100 Mbps Base-T
Serial	2× RJ45 · up to 1 Mbps · RS-232/422/485
Micro-USB	On-the-Go · +5 Vdc @ 500 mA
RF	TNC · 50 Ω
GPS	SMA (plastic) · TNC (metal) · 50 Ω
Standard I/O	1× MMS · 2× DI

ENVIRONMENTAL & MECHANICAL

Op. Temp.	-40 °C to +75 °C (ISM) -40 °C to +60 °C (MAS)
Humidity	95% @ +40 °C, non-condensing
Dimensions	6.62 × 3.45 × 1.83 in (metal) 5.5 × 3.5 × 1.5 in (plastic)
Weight	700 g (metal) · 182 g (plastic)
Safety	UL Class I, Div 2

TRANSMITTER

	ISM
Frequency Range	2402 to 2478 MHz
Output Power	10 to 1000 mW (+10 to +30 dBm)
Modulation	MSK, BPSK, QPSK, 8PSK, 16PSK, 16QAM, 32QAM, 64QAM
Data Rate	57 to 5303 kbps
Channel Bandwidth	77, 154, 207, 310, 600, 1200 kHz
Frequency Stability	1.0 ppm
Range	24 miles

Receiver Specifications

ISM · 2402–2478 MHz

Modulation	Sensitivity	Data Rate
77 kHz channel		
MSK	-110 dBm	57 kbps
154 kHz channel		
MSK	-107 dBm	114 kbps
207 kHz channel		
MSK	-106 dBm	153 kbps
310 kHz channel		
MSK	-103 dBm	229 kbps
600 kHz channel		
BPSK	-98 dBm	530 kbps
QPSK	-99 dBm	1061 kbps
8PSK	-96 dBm	1591 kbps
16QAM	-91 dBm	2121 kbps
32QAM	-85 dBm	2651 kbps
64QAM	-80 dBm	3182 kbps

Modulation	Sensitivity	Data Rate
1200 kHz channel		
BPSK	-100 dBm	884 kbps
QPSK	-96 dBm	1768 kbps
8PSK	-90 dBm	2651 kbps
16PSK	-84 dBm	3535 kbps
16QAM	-85 dBm	3535 kbps
32QAM	-80 dBm	4419 kbps
64QAM	-77 dBm	5303 kbps

Sensitivity shown with FEC disabled. Enabling FEC can improve sensitivity by 3 dB.

Functionality

Networking	
Operating Modes	Point-to-Point, Point-to-MultiPoint, Enhanced MultiPoint, Peer-to-Peer, Full Duplex, Mesh
Roles	Access Point, Endpoint, Repeater (store-and-forward)
Networking	Static IP Routing, Net Filtering, Port Forwarding, Masquerading, Network Address Translation, Modbus Bridging, BATMAN Mobile Ad-hoc Networking
Protocols	IEEE 802.3, TCP, UDP, ARP, DHCP, NTP, STP, FTP, ICMP, HTTP, HTTPS, SSH, Telnet, Multicast, SNMP
Management	Web GUI, SNMP v1, v2a, v3
VLANs	802.1Q VLANs and Trunks, QoS
Quality of Service	Four levels of VLAN QoS
Serial Services	TCP/UDP Terminal Server, TCP Terminal Client, up to 5 simultaneous connections
Reliability & Security	
Error Handling	CRC, FEC, Retransmit on error
Error Correction	Golay, Reed-Solomon
Data/RF Encryption	128- & 256-bit AES, payload only or payload and RF
Hop Patterns	10 pseudo-random, 1 pseudo-random based on Network ID, and 1 secure
Secure Hop Pattern	128- & 256-bit AES hop-pattern determination
Compression	Low, High, Decompress Only
Network Performance & Diagnostics	
MultiMaster	Synchronization of collocated Access Points or multiple Access Points within a network
MultiSpeed	Up to 4 data rates within the same channel bandwidth
Diagnostics	Neighbor List, RF Ping, RF Throughput, RF Statistics, Spectrum Analyzer, IP Ping, Traceroute, IPERF, TCP Dump, DNS Lookup, Network / VPN / Serial / Modbus Bridging Statistics, statistics graphing and CSV download
Options	
Programmable I/O	Optional 8 programmable input/output signals (4 independently programmed analog inputs/outputs or digital inputs, and 4 independently programmed digital inputs/outputs)
Dual Radio	Optional dual radio with the same or different frequency bands
Integrated GPS	Optional integrated GPS

Ordering Information

Part Number	Frequency	Enclosure	Eth / Serial	I/O	Band
Single-Channel Radios					
XETAEC24-22IMDFB	2.4 GHz	Metal	2 / 2	2 DI, 1 MMS	ISM
XETAEC24-22IMDFB-IO	2.4 GHz	Metal	2 / 2	8 I/O, 1 MMS	ISM
XETAEC24-22IPDFB	2.4 GHz	Plastic	2 / 2	2 DI, 1 MMS	ISM
XETAEC24-22IPDFB-IO	2.4 GHz	Plastic	2 / 2	8 I/O, 1 MMS	ISM
Mixed-Band Dual-Channel Radios					
XETAEC9X24-22IMDFC	902–928 MHz + 2.4 GHz	Metal	2 / 2	2 DI, 1 MMS	ISM
Radios with Integrated GPS					
XETAEC24XG-22IPDFB	2.4 GHz	Plastic	2 / 2	2 DI, 1 MMS	ISM
XETAEC24XG-22IPDFB-IO	2.4 GHz	Plastic	2 / 2	8 I/O, 1 MMS	ISM

Specifications subject to change without notice. **Rev. 11.2026**