

The **Xeta2 Linux** Ethernet radio is an extremely capable and flexible industrial software defined radio covering the 217 to 220 MHz frequency band. The **Xeta2 Linux** Ethernet radio is offered with an option to include 8 programmable inputs and outputs. The **Xeta2** is based on the XetaWave patented **Dual Decode Digital Architecture™** that offers significant receiver performance.

The **Xeta2** supports multiple modulation schemes and features that can selectively switch to achieve optimal data throughput given the available channel size and environmental noise.

**MultiSpeed MultiPoint™** mode enables Endpoints operating at different over-the-air data transfer rates to communicate with a single Access Point over the same network. The **Enhanced MultiPoint, XetaEMP**, mode provides an increase in throughput and decrease in latency over our standard modes and against competitive products.



## Key Features

**High Speed** Over-the-air data transfer rates from 9 to 960 kbps plus higher throughput with payload compression and in the **XetaEMP** mode.

**Selective Modulation** Multiple MSK, PSK, and QAM modulations.

**Dual Mode** Duplex and single channel operations.

**Network Types** Point to Point, Point to MultiPoint, CSMA peer to peer, Enhanced MultiPoint (**XetaEMP**).

**Adjustable RF Output** 10 mW to 5 Watts (+10 to +37 dBm) RF output.

**Secure** Over-the-air data encryption using 128-bit and 256-bit AES.

**MultiSpeed Multipoint** Access Points communicate with Endpoints operating at different RF Data Rates.

**XetaEMP** An enhanced Point to MultiPoint protocol with increased throughput and decreased latency.

# Xeta2 Linux Specifications

| Transmitter         | Part 90                              | Part 90 Subpart T | Part 80                      |
|---------------------|--------------------------------------|-------------------|------------------------------|
| Frequency Range     | 217 to 220 MHz                       | 220 to 222 MHz    | 217 to 218 & 219 to 220 MHz  |
| Output Power        | 10 to 2000 mW (10 to 33 dBm)         |                   | 10 to 5000 mW (10 to 37 dBm) |
| Modulation          | MSK, QSPK, 8PSK, 16QAM, 32QAM, 64QAM |                   |                              |
| Data Rate           | 10 to 216 kbps                       | 9 to 480 kbps     | 153 to 960 kbps              |
| Channel Bandwidth   | 12.5, 25 & 50 kHz                    | 15, 50 & 100 kHz  | 200 & 250 kHz                |
| Frequency Stability | 1.0 ppm                              |                   |                              |
| Range               | 70+ miles                            |                   |                              |

## Part 90

| Receiver   | 12.5 kHz Channel |           | 25 kHz Channel |           | 50 kHz Channel |           |
|------------|------------------|-----------|----------------|-----------|----------------|-----------|
| Modulation | Sensitivity      | Data Rate | Sensitivity    | Data Rate | Sensitivity    | Data Rate |
| MSK        | -115 dBm         | 10 kbps   | -114 dBm       | 18 kbps   | -109 dBm       | 43 kbps   |
| QPSK       | -113 dBm         | 17 kbps   | -112 dBm       | 29 kbps   | -106 dBm       | 72 kbps   |
| 8PSK       | -107 dBm         | 26 kbps   | -106 dBm       | 44 kbps   | -103 dBm       | 105 kbps  |
| 16QAM      | -104 dBm         | 36 kbps   | -103 dBm       | 59 kbps   | -100 dBm       | 144 kbps  |
| 32QAM      | -102 dBm         | 45 kbps   | -100 dBm       | 76 kbps   | -97 dBm        | 180 kbps  |
| 64QAM      |                  | 54 kbps   |                | 91 kbps   |                | 216 kbps  |

## Part 90 Subpart T

| Receiver   | 15 kHz Channel |           | 50 kHz Channel |           | 100 kHz Channel |           |
|------------|----------------|-----------|----------------|-----------|-----------------|-----------|
| Modulation | Sensitivity    | Data Rate | Sensitivity    | Data Rate | Sensitivity     | Data Rate |
| MSK        | -115 dBm       | 9 kbps    | -105 dBm       | 36 kbps   |                 | 76 kbps   |
| QPSK       | -110 dBm       | 19 kbps   | -101 dBm       | 59 kbps   |                 | 160 kbps  |
| 8PSK       | -95 dBm        | 28 kbps   | -95 dBm        | 88 kbps   |                 | 240 kbps  |
| 16QAM      | -90 dBm        | 37 kbps   | -88 dBm        | 117 kbps  |                 | 320 kbps  |
| 32QAM      | -88 dBm        | 47 kbps   | -85 dBm        | 146 kbps  |                 | 400 kbps  |
| 64 QAM     |                | 56 kbps   |                | 176 kbps  |                 | 480 kbps  |

## Part 80

| Receiver   | 200 kHz Channel |           | 250 kHz Channel |           |
|------------|-----------------|-----------|-----------------|-----------|
| Modulation | Sensitivity     | Data Rate | Sensitivity     | Data Rate |
| MSK        | -102 dBm        | 153kbps   | -102 dBm        | 194 kbps  |
| QPSK       | -100 dBm        | 320 kbps  |                 |           |
| 8PSK       | -89 dBm         | 480 kbps  |                 |           |
| 16QAM      | -88 dBm         | 640 kbps  |                 |           |
| 32QAM      | -86 dBm         | 800 kbps  |                 |           |
| 64 QAM     |                 | 960 kbps  |                 |           |

# Xeta2 Linux Specifications

## Power

|          |                                     |
|----------|-------------------------------------|
| Transmit | 460 mA (2W) & 620 mA (5W) @ +12 Vdc |
| Receive  | 300 mA @ +12 Vdc                    |
| Idle     | 176 mA @ +12 Vdc                    |

## Interfaces

|                 |  |
|-----------------|--|
| Power Connector | 2-pin Phoenix / +12 to +32 Vdc         |
| Ethernet        | 2 x RJ45 / 10/100 Mbps Base-T          |
| Serial          | 2 x RJ45 / up to 1Mbps / RS232/422/485 |
| Micro USB       | On-the-Go; +5 Vdc @ 500 mA             |
| RF Connector    | TNC / 50 Ohms                          |

## Environmental/Physical

|                    |                            |
|--------------------|----------------------------|
| Op. Temperature    | -40°C to +75°C             |
| Humidity           | 95% @ +40°C non-condensing |
| Safety             | UL Class 1 Div 2           |
| Dimensions (LxWxH) | 6.62" x 3.45" x 1.83"      |
| Weight             | 700 grams                  |

## Functionality

|                    |  |
|--------------------|--|
| Operating Modes    | Point to Point, Point to MultiPoint, Enhanced MultiPoint, Peer to Peer   |
| Roles              | Access Point, Endpoint, Repeater   |
| Networking         | Static IP Routing, Net Filtering, Port Forwarding, Network Address Translation, Modbus Bridging  |
| Protocols          | IEEE 802.3, TCP, UDP, ARP, DHCP, NTP, FTP, ICMP, HTTP, HTTPS, SSH, Telnet, Multicast SNMP, Radius  |
| Management         | Web GUI, SNMP v1, v2, & v3, SNMP Traps   |
| VLANs              | 802.1q VLANs and Trunks, QoS   |
| Quality of Service | Four Levels of VLAN QoS  |
| Serial Services    | TCP/UDP Terminal Server, TCP Terminal Client, Multicast Terminal, Modbus Bridging  |
| Error Handling     | CRC, FEC, Retransmit on error  |
| Error Correction   | Golay, Reed-Solomon  |
| Data Encryption    | 128 & 256-bit AES Payload Data Encryption  |
| RF Encryption      | 128-bit AES RF Overhead Encryption   |
| Compression        | Decompress Only, Low, High   |
| Repeater           | Store-and-forward  |
| MultiMaster        | Synchronization of Collocated Access Points or Multiple Access Points within a Network   |
| MultiSpeed         | Up to 4 Data Rates within the Same Channel Bandwidth   |
| Diagnostics        | Neighbor List, RF Ping, RF Throughput, RF Statistics, IP Ping, Traceroute, DNS Lookup, Serial Statistics, Modbus Bridging Statistics, Network Statistics, Forwarding Table, Route Table, ARP Table, Channel Utilization, IO Status |
| Programmable I/O   | Option for 8 programmable input/output signals (4 independently programmed analog inputs, analog outputs, or digital inputs and 4 independently programmed digital inputs or digital outputs)                                      |
| Dual Radio         | Option for dual radio that has the same or different frequency band  |

# Xeta2 Linux Specifications

## Ordering

|                    |   |
|--------------------|---|
| XETA2-22MMLFB      | Metal Enclosed, 2 Ethernet & 2 Serial                                     |
| XETA2-22MMLFB-IO   | Metal Enclosed, 2 Ethernet & 2 Serial with 8 Programmable I/O             |
| XETA2X2-22MMLFB    | Metal Enclosed, Dual Radio, 2 Ethernet & 2 Serial                         |
| XETA2X2-22MMLFB-IO | Metal Enclosed, Dual Radio, 2 Ethernet & 2 Serial with 8 Programmable I/O |